

In the Claims:

1. (Currently Amended) A computing device comprising:

a display that is deflectable;

a memory to store a data collection, the data collection corresponding to a plurality of pages that are associated together in a sequence to form a paginated content, wherein each page is individually presentable on the display;

a processor coupled to the display and the memory, the processor being configured to use data from the collection of data to present one or more pages from the plurality of pages on the display; and

a sensor device coupled to the processor to measure a an analog value corresponding to a deflection of the display;

wherein the processor uses the sensor device to determine a deflection value that coincides with the measured deflection of the display, and

wherein the processor is configured to use the deflection value to determine at least a rate at which at least portions of individual pages in the plurality of pages are presented in a sequence on the display; and

wherein the processor displays during an interval at least portions of a current page and a subsequent page, the subsequent page having a proximity to the current page in a pre-determined order of the data collection, and wherein the analog value indicates the proximity of the subsequent page to the current page.

CLAIMS 2-3: Previously Cancelled

CLAIM 4. CANCEL

5. (Previously Amended) The computing device of claim 1, wherein the sensor device is integrated with the display.

6. (Original) The computing device of claim 5, wherein at least a first area of the display is overlaid on the sensor device to deflect with the sensor device.

7. (Previously Amended) The computing device of claim 5, wherein the sensor device is deflectable, and wherein the display is deflectable to be able to bend with the sensor device.

8. (Currently Amended) The computing device of claim 4~~1~~, wherein the analog value correlates to a magnitude of the deflection.

9. (Original) The computing device of claim 8, wherein the magnitude of the deflection determines a frequency at which the portions of the multiple pages are presented on the display.

CLAIM 10. CANCEL

11. (Currently Amended) The computing device of claim 10~~1~~, wherein a length of the interval is determined by the analog value.

12. (Previously Amended) The computing device of claim 11, wherein the interval corresponds to when the display is deflected.

13. (Currently Amended) The computing device of claim-41, further comprising an analog to digital converter to signal the processor a digital value corresponding to the analog value measured by the sensor device.

14. (Original) The computing device of claim 1, further comprising a digitizer coupled to the display.

15. (Original) The computing device of claim 14, wherein the sensor device is unitarily formed with the digitizer.

16. (Original) The computing device of claim 14, wherein the display is overlaid on the digitizer, and the sensor device is connected to the digitizer and positioned underneath the digitizer.

17. (Currently Amended) A computing device comprising:

a deflectable display;

a memory to store a data collection, the data collection representing a plurality of pages that are associated together in a sequence to form a paginated content, wherein each page is independently presentable on the display;

a processor coupled to the display and the memory, the processor configured to use data from the data collection to present at least portions of one or more pages from the plurality of pages; and

a sensor device coupled to the display to detect a deflection of the display, the sensor device communicating a deflection value corresponding to the deflection of the display to the processor;

wherein the processor is configured to use the deflection value to identify a set of pages in the plurality of pages, and based on the deflection value, the processor sequentially presents at least portions from one or more pages in the identified set of pages on a first area of the display;

wherein a current page is presented on the display when the sensor device detects the deflection of the display, and wherein the processor identifies the set of pages using the deflection value;

wherein the display includes a plurality of discrete elements, and wherein for each page, the memory stores a value to the discrete elements of the display when that page is presented on the display;

wherein the first area of the display includes discrete elements that are sequentially assigned values from the select pages in the set of pages; and

wherein a second area of the display includes discrete elements that are assigned values from a current page while the discrete elements of the first area are sequentially assigned values from the select pages in the set of pages.

CLAIMS 18-21: CANCEL

22. (Currently Amended) The computing device of claim ~~21~~17, wherein the select pages in the identified set appears sequentially on the first portion of the display according to a predetermined order of the plurality of pages.

23. (Original) The computing device of claim 17, wherein the processor is configured to sequentially assign the discrete elements in the first area of the display corresponding

values stored for select pages in the data collection so that the discrete elements are sequentially assigned values from one of the select pages in the identified set of pages.

24. (Original) The computing device of claim 17, wherein the processor sequentially assigns values to each of the discrete elements in the first area of the display while the display is being deflected, the value assigned to each discrete element corresponding to one of the select pages in the identified set of pages.

25. (Original) The computing device of claim 17, wherein for each of the select pages, the processor signals only some of the discrete elements in the first area of the display values from that page.

26. (Original) The computing device of claim 25, wherein the plurality of discrete elements are arranged into rows and columns to form the display, and the processor assigns only some of the rows in the first area of the display values stored with each of the multiple pages.

CLAIMS 27-37: CANCEL

38. (Previously Amended) A peripheral device for a handheld computer, the handheld computer comprising a display, a processor coupled to the display, and a memory, wherein the memory stores a data collection that represents a plurality of pages that are associated together in a sequence to form a paginated content, wherein each page is independently presentable on the display, wherein the processor is configured to access the memory and to signal the display to individually present one or more of the plurality of pages, wherein the peripheral device comprises:

a communication port to extend communications between the peripheral device and the handheld computer; and

an analog input device coupled to the processor of the handheld computer via the communication port, the analog input device including a deflectable sensor device that signals a deflection value to the processor when deflected, the deflection value causing the processor to sequentially display at least portions of multiple pages from the plurality of pages on at least a portion of the display of the handheld computer;

wherein the analog input device generates data to enable the processor to display during the interval at least portions of a current page and a subsequent page, the subsequent page having a proximity to the current page in a pre-determined order of the data collection, and wherein the analog value determines the subsequent page by determining the proximity of the subsequent page to the current page based on the deflection value.

47. (Currently Amended) A computing device comprising:

a display;

a memory to store a data collection, the data collection representing a plurality of pages that are associated together in a sequence to form a paginated content, wherein each page is independently presentable on the display;

a processor coupled to the display and the memory, the processor being configured to use the data in the data collection to present the pages on the display; and

a sensor device coupled to the processor, the sensor device sensing a deflection of a member to signal the processor a deflection value, the deflection value causing the processor to sequentially present at least portions of multiple pages on the display over

an interval of time, wherein a rate at which at least portions of individual pages of the multiple pages are displayed is based at least in part on the deflection value;

wherein the display is deflectable and coupled to the sensor device so as to deflect with the sensor device; and

wherein the processor displays during the interval at least portions of a current page and a subsequent page, the subsequent page having a proximity to the current page in a pre-determined order of the data collection, and wherein the analog value determines the subsequent page by determining the proximity of the subsequent page to the current page, the proximity being based at least in part by the deflection value.

48. (Previously Added) The computing device of claim 47, wherein the member is a component of the sensor device.

49. (Previously Added) The computing device of claim 47, wherein the sensor device measures an analog value corresponding to a deflection of the sensor device.

50. (Previously Added) The computing device of claim 47, wherein the sensor device is integrated with the display.

51. (Previously Added) The computing device of claim 50, wherein at least a first area of the display is overlaid on the sensor device to deflect with the sensor device.

52. (Currently Amended) The computing device of claim 50, wherein the e_display is deflectable so as to be able to bend with the sensor device.

53. (Previously Added) The computing device of claim 49, wherein the analog value correlates to a magnitude of the deflection.

54. (Previously Added) The computing device of claim 53, wherein the magnitude of the deflection determines a frequency at which the portions of the multiple pages are presented on the display.

CLAIM 55: CANCEL

56. (Previously Added) The computing device of claim 55, wherein a length of the interval is determined by the analog value.

57. (Previously Added) The computing device of claim 56, wherein the interval corresponds to when the display is deflected.

58. (Previously Added) The computing device of claim 49, further comprising an analog to digital converter to signal the processor a digital value corresponding to the analog value measured by the sensor device.

59. (Previously Added) The computing device of claim 47, further comprising a digitizer coupled to the display.

60. (Previously Added) The computing device of claim 59, wherein the sensor device is unitarily formed with the digitizer.

61. (Previously Added) The computing device of claim 59, wherein the display is overlaid on the digitizer, and the sensor device is connected to the digitizer and positioned underneath the digitizer.

Claims 62-64: Previously Cancelled